



ESCHBACH MONOFLEX S



Semi rigid booster hose

Lightweight attack hose for municipal and wildfire applications. Available in fluorescing orange for supreme visibility. Circular woven jacket out of 100% high tenacity synthetic yarn and monofile with an inner liner made out of a vulcanized high quality EPDM compound.

ADVANTAGES

- Lightweight compared to rubber hoses
- Low friction loss
- High aging resistance
- Easy maintenance and handling



APPROVALS

- DIN EN 1947-II-B-5

SERVICE

- Standard colours orange and blue, other colours on request
- Binding with international couplings on request
- Hand and anti-kink protection on request
- Standard length 50 m, other lengths on request

Diameter Inch (mm)	Weight g/m	Burst pressure bar	Working pressure bar	Test pressure bar	Certificate Number
1" (25)	250	45*	15	30	ZPC 30005

Monoflex S HD

Diameter Inch (mm)	Weight g/m	Burst pressure bar	Working pressure bar	Test pressure bar	Certificate Number
1" (25)	250	100	40	60	ZPC 30005

* according to DIN EN 1947, the real burst pressure is higher.

Remark maximum working pressure:

The mentioned data is valid for the hose only. In case of fitted couplings the working pressure depends on the respective defined nominal pressure of the used coupling and the method of fitting.